

Safety data sheet

CONSTRUCTION GROUT RC

Revision date : 2009/04/01
Version: 1.0

Page: 1/6
(30367298/SDS_GEN_US/EN)

1. Substance/preparation and company identification

Company

BASF Construction Chemicals
100 Campus Drive
Florham Park, NJ 07932

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
14808-60-7	40.0 - 70.0 %	crystalline silica
65997-15-1	15.0 - 40.0 %	Cement, portland, chemicals
1309-37-1	1.0 - 5.0 %	Iron oxide
1305-78-8	1.0 - 5.0 %	calcium oxide
7778-18-9	1.0 - 5.0 %	Calcium sulphate
112945-52-5	0.5 - 1.5 %	Silica

3. Hazard identification

Emergency overview

WARNING: CONTAINS MATERIAL WHICH CAN CAUSE CANCER.
MAY BE HARMFUL IF INHALED.
MAY CAUSE ALLERGIC SKIN REACTION.
Can cause moderate irritation due to abrasive action.
In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.
Keep container tightly closed.
Avoid inhalation of dusts.
Avoid ingestion.
Avoid contact with the skin, eyes and clothing.
Wash thoroughly after handling.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

No data available.

Irritation:

Information on: calcium oxide
Corrosive! Damages skin and eyes.

Sensitization:

Safety data sheet

CONSTRUCTION GROUT RC

Revision date : 2009/04/01
Version: 1.0

Page: 2/6
(30367298/SDS_GEN_US/EN)

May cause allergic skin reaction.

Repeated dose toxicity:

Information on: Iron oxide

Chronic exposures have been known to produce pneumoconiosis (chronic inflammatory and fibrotic lung disease).

The substance may cause increase in lung mass and lung tissue changes after repeated inhalation.

The product has not been tested. The statement has been derived from products of a similar structure and composition.

4. First-aid measures

If inhaled:

After inhalation of dust. Keep patient calm, remove to fresh air. If difficulties occur: Obtain medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

5. Fire-fighting measures

Lower explosion limit:	not available
Upper explosion limit:	not available
Flammability:	not self-igniting
Self-ignition temperature:	not self-igniting

Suitable extinguishing media:

foam, water spray, dry extinguishing media, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:

Avoid dust formation. Avoid contact with skin and eyes. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Safety data sheet

CONSTRUCTION GROUT RC

Revision date : 2009/04/01
Version: 1.0

Page: 3/6
(30367298/SDS_GEN_US/EN)

Cleanup:

Avoid raising dust.

For small amounts: Pick up with suitable appliance and dispose of. Dispose of absorbed material in accordance with regulations.

For large amounts: Pick up with suitable appliance and dispose of. Dispose of absorbed material in accordance with regulations.

7. Handling and storage

Handling

General advice:

Avoid dust formation. Avoid inhalation of dusts. Avoid skin contact. Pour downwind and allow as little free fall as possible while emptying bags into equipment. Breathing must be protected when large quantities are decanted without local exhaust ventilation.

Protection against fire and explosion:

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Keep away from sources of ignition - No smoking. Dust can form an explosive mixture with air.

Storage

Storage incompatibility:

General: Segregate from metals. Segregate from acids. Segregate from lyes. Segregate from oxidants. Segregate from foods and animal feeds.

Temperature tolerance

Protect from temperatures below: 5 °C

Protect from temperatures above: 35 °C

8. Exposure controls and personal protection

Components with workplace control parameters

crystalline silica	OSHA	TWA value 2.4 millions of particles per cubic foot of air Respirable ; TWA value 0.1 mg/m3 Respirable ; TWA value 0.3 mg/m3 Total dust ;
Cement, portland, chemicals	ACGIH	TWA value 0.025 mg/m3 Respirable fraction ;
	OSHA	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ;
Iron oxide	ACGIH	TWA value 10 mg/m3 ;
	ACGIH	TWA value 5 mg/m3 Respirable fraction ;
calcium oxide	OSHA	PEL 5 mg/m3 ;
	ACGIH	TWA value 2 mg/m3 ;
Calcium sulphate	OSHA	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ;
	ACGIH	TWA value 10 mg/m3 Inhalable fraction ;

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate.

Hand protection:

Chemical resistant protective gloves, Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Safety data sheet

CONSTRUCTION GROUT RC

Revision date : 2009/04/01
Version: 1.0

Page: 4/6
(30367298/SDS_GEN_US/EN)

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and chemical properties

Form:	powder	
Odour:	odourless	
Colour:	grey	
Melting point:		not applicable
Relative density:		No data available.
Viscosity, dynamic:		not applicable
Solubility in water:		miscible

10. Stability and reactivity

Conditions to avoid:

Avoid dust formation.

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Corrosion to metals:

No data available.

Oxidizing properties:

not fire-propagating

11. Toxicological information

Acute toxicity

Oral:

LD50/ > 5,000 mg/kg
No systemic toxicity

Skin irritation:

Irritant.

Eye irritation :

Risk of serious damage to eyes.

Carcinogenicity:

Information on: crystalline silica

The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

Safety data sheet

CONSTRUCTION GROUT RC

Revision date : 2009/04/01
Version: 1.0

Page: 5/6
(30367298/SDS_GEN_US/EN)

12. Ecological information

Environmental fate and transport

Biodegradation:

Evaluation: Non-biodegradable.

Environmental toxicity

Other ecotoxicological advice:

Do not discharge product into the environment without control. Due to the pH-value of the product, neutralization is generally required before discharging sewage into treatment plants. Do not release untreated into natural waters.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations.
Recommendations: Use excess product in an alternate beneficial application.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport information

Land transport USDOT

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US released / listed

Safety data sheet

CONSTRUCTION GROUT RC

Revision date : 2009/04/01

Page: 6/6

Version: 1.0

(30367298/SDS_GEN_US/EN)

OSHA hazard category: IARC 1, 2A or 2B carcinogen, NTP listed carcinogen, Chronic target organ effects reported, Acute target organ effects reported, OSHA PEL established, ACGIH TLV established, Skin and/or eye irritant

SARA hazard categories (EPCRA 311/312): Acute, Chronic

State regulations

State RTK

CAS Number

14808-60-7

65997-15-1

1305-78-8

7778-18-9

Chemical name

crystalline silica

Cement, portland, chemicals

calcium oxide

Calcium sulphate

State RTK

MA, NJ, PA

MA, NJ, PA

MA, NJ, PA

MA, PA

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

16. Other information

HMIS III rating

Health: 2 $\frac{1}{2}$

Flammability: 0

Physical hazard: 1

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

BASF Construction Chemicals

bcc_prps@basf.com

END OF DATA SHEET