

**AS-475 GROUT – IRD, INC.
MATERIAL SAFETY DATA SHEET
A COMPONENT**

SECTION 1 - PRODUCT IDENTIFICATION AND USE

Product Identifier: AS-475 Grout for IRD, Inc.

EXTRUSION LIQUID COMPONENT

Product Identification Number (PIN): UN 1866

Product Use: Installation of weigh and motion sensors.

Manufactured and Supplied By: Lafrentz Road Marking
A Division of Canadian Road Builders Inc.
1-26228 Township Road 530A
Acheson, Alberta T7X 5A7

24-Hour Emergency Telephone Number: (613) 996-6666

SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	%	CAS NUMBER	LD50 OF INGREDIENT	LC 50 OF INGREDIENT
METHYL METHACRYLATE	8 - 10	80-62-6	7872 mg/kg	not applicable
2 ETHYLHEXYL ACRYLATE	4 - 6	103-11-7	none	none

SECTION 3 - PHYSICAL DATA

PHYSICAL STATE:	THICK LIQUID
ODOUR AND APPEARANCE:	STRONG CHARACTERISTIC ODOUR THICK LIQUID, COLOUR AS ON LABEL
ODOUR THRESHOLD:	LESS THAN 1 PPM
VAPOUR PRESSURE:	47 mbar
VAPOUR DENSITY:	3.45 of MMA (AIR = 1)
EVAPORATION RATE:	not available
BOILING POINT:	100 DEGR C.
FREEZING POINT:	-48 DEGR C.
PH:	not applicable
SPECIFIC GRAVITY:	2.0 g/ml
COEFF. WATER/OIL DIST.	Not applicable

SECTION 4 - FIRE AND EXPLOSION DATA

FLAMMABILITY:	YES, SOMEWHAT FLAMMABLE
UNDER FOLLOWING CONDITIONS:	WHEN AN OPEN FLAME IS INTRODUCED THE PRODUCT WILL BURN SLOWLY. FIRE GOES OUT WHEN FLAME IS TAKEN AWAY.
MEANS OF EXTINCTION:	WATER SPRAY, FOAM, and CARBON DIOXIDE DRY CHEMICAL
FLASHPOINT:	17 DEGREES C.
UPPER FLAMMABILITY LIMIT:	12.5 (% by volume)
LOWER FLAMMABILITY LIMIT:	2.1 (% by volume)
AUTOIGNITION TEMPERATURE:	280 DEGREES C.
HAZARDOUS COMBUSTION PRODUCTS:	CO ₂ ; CO
SENSITIVITY TO IMPACT:	NONE
SENSITIVITY TO STATIC DISCHARGE:	NONE

SECTION 5 - REACTIVITY DATA

CHEMICAL STABILITY:	AVOID HEAT, LIGHT AND DIRECT SUNLIGHT METHYL METHACRYLATE MONOMER (MMA) TENDS TO SELF-POLYMERIZATION WITH HEAT BUILD-UP (EXOTHERMIC REACTION).
INCOMPATIBLE MATERIALS:	RADICAL SOURCES SUCH AS PEROXIDES, AZO COMPOUNDS, HEAVY METAL IONS, REDOX-SYSTEMS, AMINES, SULPHUR COMPOUNDS. MMA ACTS AS A STRONG SOLVENT AND CAN SOFTEN SOME PLASTIC, PAINT & RUBBER.
CONDITIONS OF REACTIVITY:	MMA HAS AN INHIBITOR AGAINST SELF- POLYMERIZATION. OXYGEN OF AIR IMPROVES THE EFFICIENCY OF THE INHIBITOR. AVOID STORAGE UNDER OXYGEN FREE ATMOSPHERE.
POSSIBLE HAZARDOUS DECOMPOSITION PRODUCTS:	NOT AVAILABLE

SECTION 6 - TOXICOLOGICAL PROPERTIES

ROUTES OF ENTRY	
SKIN CONTACT:	YES
SKIN ABSORPTION:	YES
EYE CONTACT:	YES
INHALATION:	YES
INGESTION:	YES
ACUTE OVER EXPOSURE EFFECTS:	MAY BE IRRITATING AFTER SWALLOWING, SKIN ONTACT OR INHALATION
CHRONIC OVER EXPOSURE EFFECTS:	DERMATITIS
EXPOSURE LIMITS:	NOT AVAILABLE
IRRITANCY OF PRODUCT:	EYES, SKIN, RESPIRATORY TRACT, and GASTROINTESTINAL TRACT
SENSITIZATION TO PRODUCT:	BY SKIN CONTACT
CARCINOGENICITY:	NONE REPORTED
TERATOGENICITY:	NONE REPORTED
REPRODUCTIVE TOXICITY:	NONE REPORTED
MUTAGENICITY:	NONE REPORTED
SYNERGISTIC PRODUCTS:	NONE REPORTED

SECTION 7 - PREVENTATIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT:

GLOVES:	RUBBER OR PVA
RESPIRATORY:	ORGANIC VAPOUR/ACID
EYES:	GOGGLES
FOOTWEAR:	NOT APPLICABLE
CLOTHING:	NO SPECIAL CLOTHING
OTHER:	SAFETY SHOWERS & EYE WASH SYSTEMS

ENGINEERING CONTROLS: USE OUTDOORS. EXHAUST VENTILATION RECOMMENDED WHEN USED INDOORS.

LEAK AND SPILL PROCEDURE: ADD B.P.O. 3% BY WEIGHT AND MIX IN THOROUGHLY. PEEL OFF WHEN LIKE PUTTY, THEN LANDFILL.

WASTE DISPOSAL: ADD 1% B.P.O. POWDER SPREAD OUT NOT MORE THAN 3 CM. THICK, LANDFILL WHEN HARD.

HANDLING PROCEDURES AND EQUIPMENT: DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH MATERIALS.

STORAGE REQUIREMENTS: STORE IN COOL, VENTILATED AREA. KEEP AWAY FROM INCOMPATIBLE MATERIALS.

SPECIAL SHIPPING INFORMATION: CONTROLLED UNDER "TRANSPORT OF DANGEROUS GOODS" LEGISLATION AS A FLAMMABLE.

SECTION 8 - FIRST AID MEASURES

SKIN:	RINSE WITH SOAP AND WATER. REMOVE CLOTHING AND SHOES AFTER FLUSHING HAS BEGUN.
EYE:	FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.
INHALATION:	INHALATION OF VAPOURS MAY CAUSE NAUSEA, MOVE INDIVIDUAL TO FRESH AIR
INGESTION:	IF SWALLOWED, KEEP AT REST, SEEK MEDICAL ATTENTION.

SECTION 9 – DISPOSAL CONSIDERATIONS

Procedures

Waste must be disposed of in accordance with federal, state and local regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. DO NOT HEAT OR CUT THE EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH.

Do not reuse containers.

SECTION 10 – TRANSPORT INFORMATION

US DOT Hazard Classification

Proper Shipping Name:	Methyl Methacrylate monomer, stabilized
Hazard Class:	3
ID/UN Number:	UN 1866
Packing Group:	II
ERG:	127

Canadian TDG Classification

Refer to the classification US DOT

Shipment by sea IMDG/GGVSee

Class 3	EmS 3-05	UN number 1866
Marine pollutant	Packed (+/0): 0	
Packaging group	II	
Proper Shipping Name	Methyl methacrylate monomer, stabilized	
Hazardous constituent:	methyl methacrylate	

Air transport ICAO/IATA

Class 3	UN number 1866
Packaging Group	II
Proper Shipping Name	Methyl methacrylate monomer, stabilized

SECTION 11 - PREPARATION DATE OF MSDS

PREPARED BY: LAFRENTZ ROAD MARKING, A Division of Canadian Road Builders Inc. –
Production Department

DATE: December 14, 2006

PHONE NUMBER: (780) 962-7800

Notice

The data contained herein is based on information that Lafrentz Road Marking, A Division of Canadian Road Builders Inc. believes to be reliable, but no expressed or implied warranty is made with regard to the accuracy of such data or its suitability for a given situation. Such data relates only to the specific product described and not to such product in combination with any other product and no agent of Lafrentz Road Marking, A Division of Canadian Road Builders Inc. is authorized to vary any of such data. Lafrentz Road Marking, A Division of Canadian Road Builders Inc. and its agents disclaim all liability for any actions taken or forgone on reliance upon such data.