MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : WHITE CLEAN METAL PRI 9502562

IDENTIFICATION NUMBER: 7780 500 DATE PRINTED : 11/03/97

PRODUCT USE/CLASS : PRIMER/ALKYD

SUPPLIER: MANUFACTURER:

Rust-Oleum Corporation
11 Hawthorn Parkway
11 Hawthorn Parkway
Vernon Hills, Illinois
60061 USA
Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois
60061 USA

(847) 367-7700 Rust-Oleum Corp. (847) 367-7700 Rust-Oleum Corp.

Mon.-Fri, 8:00 AM-4:30 PM Mon.-Fri, 8:00 AM-4:30 PM

PREPARER: LJW, PHONE: , PREPARE DATE: 06/11/97

:	SECT	ION 2 - COMPOS	SITION/INFORMA	TION ON INGRED	IENTS	
ITEM		CHEMICAL N	VAME	CAS NU	MBER	WT/WT % LESS THAN
01	Stoddard :	Solvent		8052-41	3	30.0 %
02	Titanium l	Dioxide	13463-6	13463-67-7		
03	1,3,5-TRI	METHYLBENZENE	108-67-	108-67-8		
04	1,2,4-TRI	METHYLBENZENE	95-63-6	95-63-6		
05	Hydrocarbo	on Resin	64742-1	64742-16-1		
06	Cobalt Dr	ier	136-52-7		0.1 %	
		I	EXPOSURE LIMIT	S	. 	
	ACC	GIH	OSH	A	COMPANY	
ITEM	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	100ppm	N.E.	100ppm	N.E.	N.E.	NO
02	10 mg/m3	N.E.	15 mg/m3	N.E.	N.E.	NO
03	25 PPM	N.E.	N.E.	N.E.	N.E.	NO
04	25 PPM	N.E.	N.E.	N.E.	N.E.	NO
05	N.E.	N.E.	N.E.	N.E.	100ppm	ИО
06	N.E.	N.E.	N.E.	N.E.	N.E.	NO

(See Section 16 for abbreviation legend)

(Continued on Page 2)

SECTION 3 - HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***: Harmful if swallowed. Causes (target organ or system) damage. Causes eye irritation. Vapors irritating to eyes and respiratory tract. Combustible liquid and vapor.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. May cause headaches and dizziness.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed. Aspiration hazard if swallowed; can enter lungs and cause damage.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

PRIMARY ROUTE(S) OF ENTRY: INHALATION EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Hold eyelids apart and flush with plenty of water for at lease 15 minutes. Get medical attention.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 104 F

LOWER EXPLOSIVE LIMIT: 0.9 %
UPPER EXPLOSIVE LIMIT: 6.4 %

AUTOIGNITION TEMPERATURE: ND

EXTINGUISHING MEDIA: DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed.

(Continued on Page 3)

Preparation Date: 06/11/97 Page 3

SECTION 5 - FIRE FIGHTING MEASURES

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance.

Product: 7780

500

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling. Wash hands before eating. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing vapor or mist. Avoid contact with eyes.

STORAGE: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Keep away from heat, sparks, flame and sources of ignition. Keep container closed when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace

conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of

(Continued on Page 4)

Product: 7780 500 Preparation Date: 06/11/97 Page 4

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : 318 - 383 F VAPOR DENSITY : Is heavier than air

ODOR : SOLVENT ODOR THRESHOLD : ND

APPEARANCE : LIQUID EVAPORATION RATE: Is slower than Ether

SOLUBILITY IN H2O : SLIGHT

FREEZE POINT : ND SPECIFIC GRAVITY: 1.2445
VAPOR PRESSURE : ND pH @ 0.0 % : ND

PHYSICAL STATE : LIQUID VISCOSITY : ND

COEFFICIENT OF WATER/OIL DISTRIBUTION: ND

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Avoid all possible sources of ignition.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION PRODUCTS: By open flame, carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

COMPONENT TOXICOLOGICAL INFORMATION:

Stoddard Solvent 4900mg/kg(rat) N.E.

Titanium Dioxide N.A. N.A.

1,3,5-TRIMETHYLBENZENE RAT 1303MG/KG RAT 24MG/M^3 4HR

1,2,4-TRIMETHYLBENZENE N.E. RAT 18G/M^3 4HR

Hydrocarbon Resin N.A. N.A.

Hydrocarbon Resin N.A. N.A. Cobalt Drier NA NA

(Continued on Page 5)

Product: 7780 500 Preparation	Date: 06/11/97	Page 5			
SECTION 11 - TOXICOLOGI	CAL PROPERTIES				
	LD50	LC50			
SECTION 12 - ECOLOGICA	AL INFORMATION				
ECOLOGICAL INFORMATION: Product is a mixture of listed components.					
SECTION 13 - DISPOSAL	CONSIDERATIONS				
DISPOSAL METHOD: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter storm drains or sewer systems.					
SECTION 14 - TRANSPORTA	TION INFORMATION				
No transportation information is available.					
SECTION 15 - REGULATO	RY INFORMATION				
U.S. FEDERAL REGULATIONS: AS FOLLOWS -					
OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)					
CERCLA - SARA HAZARD CATEGORY: This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:					
IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD					
SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:					
CHEMICAL NAME 1,2,4-TRIMETHYLBENZENE XYLENE ETHYLBENZENE	CAS NUMBER WT/WT 95-63-6 1330-20-7 100-41-4	% IS LESS THAN 5.0 % 1.0 % 1.0 %			
TOXIC SUBSTANCES CONTROL ACT:					

(Continued on Page 6)

SECTION 15 - REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER No information is available.

500

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
Magnesium Silicate	14807-96-6
Alkyd Resin	66070-60-8
Chemical Composite	66402-68-4

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAM	ME CAS NUMBER
Magnesium Silicate	14807-96-6
Alkyd Resin	66070-60-8
Chemical Composite	66402-68-4

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME ------ CAS NUMBER No Proposition 65 chemicals exist in this product.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION	16	-	OTHER	INFORMATION
PECTION	T C	_	OIUPV	TMLOWNETON

HMIS RATINGS - HEALTH:

FLAMMABILITY:

REACTIVITY:

PREVIOUS MSDS REVISION DATE: 04/10/97

Product: 7780 500 Preparation Date: 06/11/97

SECTION 16 - OTHER INFORMATION

LEGEND: N.A. - Not Applicable, N.E. - Not Established,

N.D. - Not Determined

: No Information.

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

Page 7