

SECTION V-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

Acute(Inhalation): Harmful if inhaled. May affect the brain and nervous system causing dizziness, headache or nausea. Repeated overexposures may progressively lead to staggering gait, confusion, unconsciousness or coma. Causes nose and throat irritation.

Acute(Skin or Eye Contact): Causes eye and skin irritation which can lead to dermatitis with repeated overexposures.

Ingestion: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic: Reports have associated repeated prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to Xylene and Toluene in lab animals has been associated with liver, kidney, lung, spleen and eye damage as well as anemia. Effects in humans have included liver and cardiac abnormalities.

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation: Remove from exposure, restore breathing and notify a physician.

Eye Contact: Flush immediately with large amounts of water for at least 15 minutes. Notify a physician.

Skin Contact: Wash affected area with soap and water, remove contaminated clothing and wash before reuse.

Ingestion: DO NOT induce vomiting. Keep person warm, quiet and get medical attention. Aspiration of this material into the lungs can cause chemical pneumonitis which can be fatal.

SECTION VI-REACTIVITY DATA

Stability: Stable Incompatible: with strong oxidizing agents

Hazardous Decomposition Products: By open flame- Carbon monoxide & Carbon dioxide

Hazardous Polymerization: Will Not Occur

SECTION VII-SPILL OR LEAK PROCEDURES

Release or Spill Procedures: Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools

Waste Disposal Method: Dispose of according to local, state and federal regulations. DO NOT incinerate closed containers.

SECTION VIII-SPECIAL PROTECTION INFORMATION

Respiratory Protection:Use NIOSH approved chemical cartridge respirator (TC23C) to remove solid airborne overspray particles and organic vapors during spraying.

In Confined Areas: Use NIOSH approved supplied-air respirators or hoods (TC19C).

Eye Protection:Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment:Use impervious gloves and/or clothing to prevent skin contact.

Ventilation: Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients below acceptable limits.

SECTION IX-SPECIAL PRECAUTIONS AND REGULATORY ISSUES

Handling and Storage Precautions: Do not store above 120 F. DO NOT puncture or incinerate containers. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CALIFORNIA PROPOSITION 65 WARNING: These products contain chemicals known to the State of California to cause birth defects or other reproductive harm.