

# MATERIAL SAFETY DATA SHEET

## SECTION I PRODUCT IDENTIFICATION

**PRODUCT NAME:** SLIKSTYX  
**DATE PREPARED:** 04/29/02  
**PRODUCT USE:** GASKET LUBRICANT  
**PRODUCT DESCRIPTION:** AEROSOL DISPENSED YELLOW GOLD LUBRICANT LIQUID  
**MANUFACTURER'S NAME:**  
FUTURE TOOLS, INC.  
13591 CABLE ROAD  
PATASKALA, OHIO 43062  
**TELEPHONE NUMBER:** 1 800 576 9707  
**EMERGENCY PHONE NUMBER:**

## SECTION II COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS NO.	% WT.	TLV	PEL
HYDROCARBON PROPELLANT	68-476-86-8	32-40	1000PPM	1000PPM
MINERAL OIL	8042-47-5	18-24	NONE	NONE
PETROLATUM	8009-03-08	16-24	5MG/M3	5MG/M3
PROPRIETARY	N/A	4-20	NONE	NONE
SYNTHETIC ISOPARAFFINIC HYDROCARBON	64742-48-9	16-24	400PPM	N/A
b-CAROTENE	7235-40-7	<1	NONE	NONE
CORN OIL	8001-30-7	<1	NONE	NONE

## SECTION III HEALTH INFORMATION AND PROTECTION

**EYE CONTACT:** THIS PRODUCT IS MINIMALLY IRRITATING TO THE EYES UPON DIRECT CONTACT, BASED ON TESTING OF SIMILAR PRODUCT AND/OR COMPOUNDS.

**SKIN CONTACT:** THIS PRODUCT IS NOT EXPECTED TO CAUSE ANY SKIN IRRITATION UPON DIRECT SINGLE OR REPEATED AND PROLONGED CONTACT; HOWEVER MINIMAL TO SLIGHT DERMAL IRRITATION MAY OCCUR TO SENSITIVE INDIVIDUALS.

**INHALATION:** EXCESSIVE INHALATION OF VAPORS MAY CAUSE IRRITATION TO THE RESPIRATORY TRACT, DIZZINESS, HEADACHE, FATIGUE, OR ASPHYXIATION.

**INGESTION:** INGESTION IS RELATIVELY NON-TOXIC UNLESS ASPIRATION OCCURS. THIS PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS OR DIARRHEA

**HEALTH DATA:** EXPOSURE TO A LARGE SINGLE DOSE OR REPEATED SMALL DOSES OF THIS PRODUCT BY INHALATION, ASPIRATION, OR INGESTION LEADING TO ASPIRATION CAN LEAD TO LEPID PNEUMONIA OR LIPID GRANULOMA OF THE LUNG. THESE ARE LOW GRADE, CHRONIC, LOCALIZED TISSUE REACTIONS. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS. THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CONCLUDED THAT THE HIGHLY REFINED OILS IN THIS PRODUCT ARE GROUP 3 SUBSTANCES, "NOT CLASSIFIABLE AS TO THEIR CARCINOGENICITY TO HUMANS" BASED ON INADEQUATE HUMAN AND INADEQUATE ANIMAL EVIDENCE, IARC HAS ALSO CONCLUDED THAT THERE IS NO EVIDENCE FOR THE CARCINOGENICITY TO EXPERIMENTAL ANIMALS OF THESE OILS WHEN ADMINISTERED BY ROUTE OTHER THAN INTRAPERITONEAL INGESTION. THIS PRODUCT IS NOT CARCINOGENIC ACCORDING TO THE OSHA HAZARD COMMUNICATION STANDARD.

## SECTION IV. EMERGENCY AND FIRST AID PROCEDURE

**EYE CONTACT:** IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER. FLUSH ALSO UNDER EYELIDS. CONTINUE FLUSHING EYES UNTIL IRRITATION SUBSIDES. IF IRRITATION OCCURS CONSULT A PHYSICIAN IMMEDIATELY.

**SKIN CONTACT:** REMOVE ANY CONTAMINATED CLOTHING. WASH EXPOSED AREA OF SKIN WITH SOAP AND WATER. IF SKIN IRRITATION OCCURS, CONSULT A PHYSICIAN.

**INHALATION:** REMOVE TO FRESH AIR. IF ADVERSE SYMPTOMS OCCUR, GET MEDICAL ATTENTION.

**INGESTION:** DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION PROMPTLY.

## SECTION V. HEALTH PROTECTION

**EYE PROTECTION:** NONE REQUIRED. HOWEVER, EYE PROTECTION IS A GOOD INDUSTRIAL PRACTICE AND IS RECOMMENDED.

**SKIN PROTECTION:** NO SKIN PROTECTION IS REQUIRED FOR SINGLE, SHORT DURATION EXPOSURES. FOR PROLONGED OR REPEATED EXPOSURES, USE IMPERVIOUS CLOTHING TO PROTECT AREAS SUBJECT TO EXPOSURE.

**RESPIRATORY PROTECTION:** RESPIRATORY PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. AN ORGANIC VAPOR RESPIRATOR WITH A DUST AND MIST FILTER MAY BE USED. ALL RESPIRATORS MUST BE NIOSH CERTIFIED. DO NOT USED COMPRESSED OXYGEN IN HYDROCARBON ATMOSPHERES.

**VENTILATION:** GOOD ENGINEERING PRACTICES MUST BE IN PLACE TO ENSURE ADEQUATE VENTILATION TO MAINTAIN CONCENTRATIONS OF VAPORS OR MISTS BELOW SPECIFIED EXPOSURE LIMITS.

**OTHER:** CONSUMPTION OF FOOD AND BEVERAGES SHOULD BE AVOIDED IN THE WORK AREA. ALWAYS WASH HANDS AND FACE WITH SOAP AND WATER BEFORE EATING, DRINKING, OR SMOKING.

## SECTION VI. FIRE PROTECTION INFORMATION

**FLASH POINT:** -132 DEGREES F. **FLAMMABLE LIMITS** LEL=1.8 UEL=9.6

**AUTOIGNITION TEMP.:** NO DATA

**EXTINGUISHING MEDIA:** CARBON DIOXIDE, DRY CHEMICAL, MIST, WATER SPRAY, OR FOAM.

**SPECIAL FIREFIGHTING PROCEDURES:** WATER MAY BE INEFFECTIVE, BUT WATER FOG CAN BE USED TO COOL CONTAINERS. USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.

**UNUSUAL FIREFIGHTING CONDITIONS:** EXTREMELY FLAMMABLE. CONTAINERS SUBJECTED TO TEMPERATURES IN EXCESS OF 120 DEGREES F. ARE SUBJECT TO SUDDEN RELEASE OF PRESSURE AND CONTENTS, AND MAY ROCKET. DENSE SMOKE MAY BE GENERATED WHILE BURNING. CARBON DIOXIDE, CARBON MONOXIDE, AND OTHER OXIDES MAY BE GENERATED AS A PRODUCT OF COMBUSTION.

**U.F.C. LEVEL 3 AEROSOL**

## SECTION VII. REACTIVITY DATA

**STABILITY:** STABLE

**CONDITIONS TO AVOID:** HIGH HEAT, SOURCES OF IGNITION. DO NOT STORE IN DIRECT SUNLIGHT. DO NOT STORE ABOVE 120 DEGREES F.

**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR.

**MATERIALS TO AVOID:** STRONG OXIDIZING AGENTS.

**HAZARDOUS DECOMPOSITION PRODUCTS:** CARBON DIOXIDE, CARBON MONOXIDE.

## SECTION VIII. ENVIRONMENTAL PRECAUTIONS

**STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:** IN THAT THIS PRODUCT IS PACKAGED IN A SEALED AEROSOL CONTAINER, A SPILL IS UNLIKELY. A LEAKING CAN, MAY WITH CAUTION BE PLACED IN A PLASTIC BAG OR PAIL UNTIL PRESSURE HAS DISSIPATED. ALL PRECAUTIONS AND DATA FROM PREVIOUS SECTIONS IS TO APPLY. MINOR SPILLS OR LEAKAGE MAY BE ABSORBED WITH APPROPRIATE MATERIALS AND DISPOSED IN ACCORDANCE WITH LOCAL REGULATIONS. VAPORS ARE HEAVIER THAN AIR. REMOVE ALL SOURCES OF IGNITION. NOTIFY APPROPRIATE AUTHORITIES OF SPILL.

**WASTE DISPOSAL:** ALL MATERIALS MUST BE DISPOSED OF ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS. THIS MATERIAL IF SPILLED OR DISCARDED, MAY BE A REGULATED WASTE. REFER TO ALL REGULATIONS PRIOR TO DISPOSAL. WASTE MATERIAL MAY BE LANDFILLED OR DISPOSED OF AT APPROVED FACILITY. MATERIAL SHOULD BE RECYCLED IF POSSIBLE.

## SECTION IX. MISCELLANEOUS

**HANDLING AND STORAGE:** STORE IN ACCORDANCE TO LOCAL REGULATIONS. STORE AWAY FROM HEAT, SPARKS, OPEN FLAME, OR OXIDIZING MATERIALS. THIS PRODUCT IS CONSIDERED HAZARDOUS UNDER DOT REGULATIONS. SHIP AS HAZARDOUS MATERIAL, CONSUMER COMMODITY, ORM-D, AEROSOLS. DOT ID NO. UN 1950

## SECTION X. PHYSICAL PROPERTIES

**BOILING POINT(F)** : -44 - 230 F.  
**VAPOR DENSITY(AIR=1)**: <1  
**APPEARANCE**: YELLOW GOLD LIQUID  
**ODOR**: MILD  
**SOLUBILITY IN WATER**: INSOLUBLE  
**SPECIFIC GRAVITY**: .695  
**VAPOR PRESSURE**: 70 PSI @ 70 F .

### DISCLAIMER OF WARRANTY:

THE MATERIAL CONTAINED HEREIN IS BASED ON DATA AVAILABLE TO US, AND REFLECTS OUR BEST PROFESSIONAL JUDGMENT IN IT'S PREPARATION. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF SAID DATA. THE RESULTS TO BE OBTAINED FROM THE USE HEREOF, OR THAT ANY SUCH USE DOES NOT INFRINGE ANY PATENT. SINCE THE INFORMATION CONTAINED HEREIN AND/OR PRODUCT MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL AND OF WHICH WE MAY BE UNFAMILIAR, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATION. THIS INFORMATION IS PROVIDED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS/HER OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS/HER PARTICULAR PURPOSE.

---

## MATERIAL SAFETY DATA SHEET

### SECTION 1 PRODUCT IDENTIFICATION

**PRODUCT NAME**: SLIKSTYX DELUXE 221B

**DATE PREPARED**: 03/25/01

**PRODUCT USE**: GASKET LUBRICANT

**PRODUCT DESCRIPTION**: YELLOW GOLD LUBRICANT LIQUID. THIS PRODUCT SUPPLIED IN AEROSOL FORM IS NON FLAMMABLE AS DESCRIBED IN THE FEDERAL HAZ. SUBSTANCE ACT 1600CFR1500.3 (C)(6)

**PART NUMBER**:

**MANUFACTURER'S NAME**:

FUTURE TOOLS, INC.

13591 CABLE ROAD

PATASKALA, OHIO 43062

**TELEPHONE NUMBER**: 1 800 576 9707

**EMERGENCY PHONE NUMBER**: SECTION II COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS NO.	% WT.	TLV	PEL	OTHER LIMITS
1,1,1,2-TETRAFLUOROETHANE	811-97-2	30-40	NE	NE	1,000 PPM**
DIMETHYL ETHER	115-10-6	5-15	NE	NE	1,000 PPM**
PROPRIETARY	N/A	10-20	NONE	NONE	NONE
SYNTHETIC ISOPAFFINIC HYDROCARBON	64742-48-9	2-12	NONE	NONE	
MINERAL OIL	8042-47-5	30-40	NONE	NONE	
b-CAROTENE	7235-40-7	<1	NONE	NONE	
CORN OIL	8001-30-7	<1	NONE	NONE	

\*\* SUPPLIER

NOTE 1: THE PROPRIETARY INGREDIENT AND ITS SPECIFIC CHEMICAL NAME ARE WITHHELD AS TRADE SECRETS UNDER SECTION (I) OF PART 1900.1200 HAZARD COMMUNICATIONS. NONE OF THE INGREDIENTS ARE ON ANY TOXIC SUBSTANCE LIST. THEY ARE NOT NTP, NOR ARE THEY OSHA REGULATED.

## SECTION III HEALTH INFORMATION AND PROTECTION

### HEALTH HAZARD/EFFECT OF OVER EXPOSURE:

**INHALATION:** MAY CAUSE RESPIRATORY IRRITATION. HIGH VAPOR CONCENTRATIONS INCLUDING AN OXYGEN DEFICIENT ATMOSPHERE IN ENCLOSED AREA CAN AFFECT THE NERVOUS SYSTEM, AND CAUSE HEADACHE, DIZZINESS, DROWSINESS, CYANOSIS, UNCONSCIOUSNESS, AND DEATH. IN SUSCEPTIBLE INDIVIDUALS, CARDIAC SENSITIZATION CAN RESULT IN POTENTIALLY FATAL HEARTBEAT IRREGULARITIES.  
**EYE CONTACT:** THIS PRODUCT IS MINIMALLY IRRITATING TO THE EYES UPON DIRECT CONTACT, BASED ON TESTING OF SIMILAR PRODUCT AND/OR COMPOUNDS.

**SKIN CONTACT:** THIS PRODUCT IS NOT EXPECTED TO CAUSE ANY SKIN IRRITATION UPON DIRECT SINGLE OR REPEATED AND PROLONGED CONTACT; HOWEVER MINIMAL TO SLIGHT DERMAL IRRITATION MAY OCCUR TO SENSITIVE INDIVIDUALS. CONTACT WITH RAPIDLY VOLATILIZING LIQUID OR COLD VAPORS CAN CAUSE FROSTBITE OR FREEZE BURNS TO ANY TISSUE DUE TO THE CRYOGENIC (EXTREME LOW TEMPERATURE) EFFECT OF THIS PRODUCT.

**INGESTION:** INGESTION IS RELATIVELY NON-TOXIC UNLESS ASPIRATION OCCURS. THIS PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS OR DIARRHEA

**HEALTH DATA:** EXPOSURE TO A LARGE SINGLE DOSE OR REPEATED SMALL DOSES OF THIS PRODUCT BY INHALATION, ASPIRATION, OR INGESTION LEADING TO ASPIRATION CAN CAUSE LEPID PNEUMONIA OR LIPID GRANULOMA OF THE LUNG. THESE ARE LOW GRADE, CHRONIC, LOCALIZED TISSUE REACTIONS. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS. THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CONCLUDED THAT THE HIGHLY REFINED OILS IN THIS PRODUCT ARE GROUP 3 SUBSTANCES, "NOT CLASSIFIABLE AS TO THEIR CARCINOGENICITY TO HUMANS" BASED ON INADEQUATE HUMAN AND INADEQUATE ANIMAL EVIDENCE, IARC HAS ALSO CONCLUDED THAT THERE IS NO EVIDENCE FOR THE CARCINOGENICITY TO EXPERIMENTAL ANIMALS OF THESE OILS WHEN ADMINISTERED BY ROUTE OTHER THAN INTRAPERITONEAL INGESTION THIS PRODUCT IS NOT CARCINOGENIC ACCORDING TO THE OSHA HAZARD COMMUNICATION STANDARD.

## SECTION IV. EMERGENCY AND FIRST AID PROCEDURE

**EYE CONTACT:** IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER. FLUSH ALSO UNDER EYELIDS. CONTINUE FLUSHING EYES FOR FIFTEEN MINUTES AND/OR UNTIL IRRITATION SUBSIDES. IF IRRITATION OCCURS OR CONTINUES CONSULT A PHYSICIAN IMMEDIATELY.

**SKIN CONTACT:** WASH EXPOSED SKIN WITH SOAP AND WATER. REMOVE ANY CONTAMINATED CLOTHING. IF SKIN IRRITATION OCCURS, CONSULT A PHYSICIAN.

**INHALATION:** REMOVE TO FRESH AIR. IF ADVERSE SYMPTOMS OCCUR, GET MEDICAL ATTENTION.

**INGESTION:** DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION PROMPTLY.

## SECTION V. HEALTH PROTECTION

**EYE PROTECTION:** NONE REQUIRED. HOWEVER, EYE PROTECTION IS A GOOD INDUSTRIAL PRACTICE AND IS RECOMMENDED. DO NOT WEAR CONTACTS WITHOUT ADDITIONAL EYE PROTECTION.

**SKIN PROTECTION:** NO SKIN PROTECTION IS REQUIRED FOR SINGLE, SHORT DURATION EXPOSURES. FOR PROLONGED OR REPEATED EXPOSURES, USE GLOVES AND IMPERVIOUS CLOTHING TO PROTECT AREAS SUBJECT TO EXPOSURE.

**RESPIRATORY PROTECTION:** RESPIRATORY PROTECTION IS NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. AN ORGANIC VAPOR RESPIRATOR WITH A DUST AND MIST FILTER MAY BE USED. ALL RESPIRATORS MUST BE NIOSH CERTIFIED.

**VENTILATION:** GOOD ENGINEERING PRACTICES MUST BE IN PLACE TO ENSURE ADEQUATE VENTILATION TO MAINTAIN CONCENTRATIONS OF VAPORS OR MISTS BELOW SPECIFIED EXPOSURE LIMITS.

**OTHER:** CONSUMPTION OF FOOD AND BEVERAGES SHOULD BE AVOIDED IN THE WORK AREA. ALWAYS WASH HANDS AND FACE WITH SOAP AND WATER BEFORE EATING, DRINKING, OR SMOKING.

## SECTION VI. FIRE PROTECTION INFORMATION

FLASH POINT (METHOD USED): NE (AEROSOL)

FLAMMABLE LIMITS: LEL: NE UEL: NE

**EXTINGUISHING MEDIA:** USE WATER SPRAY OR FOG, CO<sub>2</sub>, DRY CHEMICAL OR WATER STREAM.

**SPECIAL FIREFIGHTING PROCEDURES:** FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS APPROVED BY NIOSH DUE TO THERMAL DECOMPOSITION PRODUCTS. USE WATER SPRAY TO KEEP CONTAINERS COOL.

**UNUSUAL FIREFIGHTING CONDITIONS:** TEMPERATURES IN EXCESS OF 120F MAY CAUSE AEROSOL CANS TO RUPTURE. ELEVATION IN TEMPERATURES ABOVE 120F CAN CAUSE SUDDEN RELEASE OF PRESSURE AND CONTAINERS MAY ROCKET.

## SECTION VII. REACTIVITY DATA AND SPECIAL PRECAUTIONS

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): MAY REACT VIOLENTLY WITH SODIUM, POTASSIUM, AND BARIUM METAL. REACTS WITH FINELY DIVIDED ALUMINUM, ZINC, AND MAGNESIUM. STRONG OXIDIZERS CAN ACCELERATE DECOMPOSITION.

HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION MAY YIELD HYDROGEN FLUORIDE, CARBON MONOXIDE, CARBON DIOXIDE AND POSSIBLE TRACES OF CARBONYL FLUORIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

## SECTION VIII. ENVIRONMENTAL PRECAUTIONS

**STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:** IN THAT THIS PRODUCT IS PACKAGED IN A SEALED AEROSOL CONTAINER, A SPILL IS UNLIKELY. A LEAKING CAN, MAY WITH CAUTION BE PLACED IN A PLASTIC BAG OR PAIL UNTIL PRESSURE HAS DISSIPATED. ALL PRECAUTIONS AND DATA FROM PREVIOUS SECTIONS IS TO APPLY. MINOR SPILLS OR LEAKAGE MAY BE ABSORBED WITH APPROPRIATE MATERIALS AND DISPOSED IN ACCORDANCE WITH LOCAL REGULATIONS. VAPORS ARE HEAVIER THAN AIR. REMOVE ALL SOURCES OF IGNITION. NOTIFY APPROPRIATE AUTHORITIES OF SPILL. SPILLS SHOULD BE CONTAINED, THEN CLEANED UP BY MOPPING OR SOAK UP WITH ABSORBENT MATERIALS.

**WASTE DISPOSAL:** ALL MATERIALS MUST BE DISPOSED OF ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS. THIS MATERIAL IF SPILLED OR DISCARDED, MAY BE A REGULATED WASTE. REFER TO ALL REGULATIONS PRIOR TO DISPOSAL. WASTE MATERIAL MAY BE LANDFILLED OR DISPOSED OF AT APPROVED FACILITY. MATERIAL SHOULD BE RECYCLED IF POSSIBLE.

## SECTION IX. PHYSICAL PROPERTIES

BOILING POINT(F) : NE  
VAPOR DENSITY(AIR=1): <1  
APPEARANCE: YELLOW GOLD LIQUID  
ODOR: MILDLY SWEET  
SOLUBILITY IN WATER: INSOLUBLE  
SPECIFIC GRAVITY: .793  
VAPOR PRESSURE@ 70 F : 71 PSI

## SECTION X. TRANSPORTATION DATA (49 CFR 172.101)

DOMESTIC SERVICE AEROSOL  
DESCRIPTION: CONSUMER COMMODITY HAZARD CLASS: ORM-D  
FREIGHT CLASS: 55  
ID NO.: NONE  
LABEL REQUIRED: CONSUMER COMMODITY (ORM-D)

## SECTION XI. SPECIAL PRECAUTIONS

CONDITIONS TO AVOID: AVOID CONTACT WITH OPEN FLAME, ELECTRIC ARCS AND CURRENT, BATTERY TERMINALS OR OTHER HOT SURFACES, WHICH COULD LEAD TO BURSTING AND SUDDEN RELEASE OF PRESSURE AND CONTENTS OF AEROSOL CONTAINER. SUCH RELEASE COULD LEAD TO FIRE, FLASH FIRE AND THERMAL DECOMPOSITION.

ELECTRICAL ARCING CAN CAUSE BURN-THROUGH (PUNCTURE) WHICH COULD RESULT IN A FLASH FIRE CAUSING SERIOUS INJURY.

DO NOT PUNCTURE, INCINERATE, OR STORE AEROSOLS ABOVE 120F.  
KEEP AWAY FROM CHILDREN.

### DISCLAIMER OF WARRANTY:

THE MATERIAL CONTAINED HEREIN IS BASED ON DATA AVAILABLE TO US, AND REFLECTS OUR BEST PROFESSIONAL JUDGMENT IN IT'S PREPARATION. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF SAID DATA. THE RESULTS TO BE OBTAINED FROM THE USE HEREOF, OR THAT ANY SUCH USE DOES NOT INFRINGE ANY PATENT. SINCE THE INFORMATION CONTAINED HEREIN AND/OR PRODUCT MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL AND OF WHICH WE MAY BE UNFAMILIAR, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATION. THIS INFORMATION IS PROVIDED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS/HER OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS/HER PARTICULAR PURPOSE.